# P/N 116F/181-55

## Industrial pumps - s. 1200

Flanged double acting pump series 412, R 18:1 - 6 gpm
or 42 lb/min, with PU seals and suction tube 37"



| | |
|---|---|
| FLUIDS | FRESH OIL \| GREASE |
| SECTORS | MANUFACTURING INDUSTRY \| MINING \| SHIPPING AND OFFSHORE |
| CERTIFICATIONS | ATEX (ZONE 2) \| ATEX (ZONE 22) |

| Features | UM | Value |
|---|---|---|
| Flow rate | | 6 gpm - 42 lb/min |
| Ratio | | 18:1 |
| Compatible fluids | | oils, lubricants and greases |
| Suction tube upper body | | carbon steel |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/2" (f) |
| Fluid outlet connection | | NPT 3/4" (f) |
| Max supply pressure | psi | 120 |
| Max air consumption 120 psi | cfm | 113 |
| Noise level | dB | 80 |
| Suitable for drums or tank | | suitable for drums 55 gal |
| Packing | No. - ft3 | 1 - 3.3 |
| Weight | lb | 43 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com


Copyright ® 2026 All rights reserved to RAASM USA, Inc