



P/N 152F/701-55

Industrial pumps - s. 1500

Flanged pump series 600, R 70:1 - 15.4 lbs/min, with
PU seals and suction tube 33.8"



FLUIDS

FRESH OIL | GREASE

SECTORS

MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		15.4 lb/min
Ratio		70:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		aluminum - carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	176
Noise level	dB	80
Suitable for drums or tank		tank
Packing	No. - ft3	1 - 7.0
Weight	lb	70

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc