



P/N 2BD/26117NHI-55

Diaphragm pumps - in polypropylene and aluminum

Diaphragm pump in aluminum and polypropylene series APPB-1 with 1" flanges, membranes in NBR, balls in Hytrel® and seats in AISI 316 stainless steel



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER | DIESEL FUEL | DEF | PAINT | CLEANING DETERGENT

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate	gpm	44,9
Ratio		1:1
Max pressure	psi	120
Max cycles for minute	cpm	300
Delivery for cycles	gallons	0,16
Max suction lift	feet (')	dry column 16 - wet column 25
Max size pumpable solids	inches (")	0,12
Max working temperature	°F	149
Noise level	dB	75
Max air consumption	cfm	56,5
Air working pressure	psi	29 ÷ 87
Air inlet connection		NPT 3/8" (f)
Air outlet connection (muffler)		NPT 1/2" (f)
Fluid inlet connection		ANSI 150 - DIN PN 10 - JIS 10K 1" (0.99") proneness to NPT 1.1/4" (f) thread
Fluid outlet connection		ANSI 150 - DIN PN 10 - JIS 10K 1" (0.99") proneness to NPT 1.1/4" (f) thread
Balls for inlet and outlet		ball valve
Membranes		NBR
Balls		Hytrel®
Seats		AISI 316 stainless steel
Packing	No. - ft3	1 - 1.1
Gross weight	lb	15

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906