



P/N 39616-55

FCS (Fluid control system)

Pulser meter for diesel with inlet/outlet NPT 1" (f)



FLUIDS SECTORS

FRESH OIL | ANTIFREEZE | DIESEL FUEL

AERONAUTIC | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | MANUFACTURING INDUSTRY

| Features | UM | Value |
|----------------------|-----------|---------------------|
| Flow rate | gpm | 31,7 |
| Compatible fluids | | diesel fuel |
| Body's material | | aluminum |
| Gear's material | | POM |
| Inlet | psi | NPT 1" (f) + flange |
| Outlet | | NPT 1" (f) + flange |
| Max working pressure | | 1015 |
| Burst pressure | | ± 200 |
| Accuracy | A | ± 0,3% |
| Pulser for gallon | | 71,5 |
| Max supply voltage | | 48 V DC max |
| Max amperage | | 0,5 |
| Max power | W | 10 |
| Net weight | lb | 3 |
| Packing | No. - ft3 | 1 - 0.2 |
| Gross weight | lb | 3 |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc