



# P/N 3CF/50111SSS-55

Diaphragm pumps - entirely in aluminum

Diaphragm pump in aluminum series AABM-2 modular with 2" flanges, membranes, balls and seats in Santoprene™



## FLUIDS

FRESH OIL | WATER | DIESEL FUEL

## SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

## CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Flow rate	gpm	153,1
Ratio		1:1
Max pressure	psi	120
Max cycles for minute	cpm	147
Delivery for cycles	gallons	1,04
Max suction lift	feet (')	dry column 16 - wet column 25
Max size pumpable solids	inches (")	0,26
Max working temperature	°F	212
Noise level	dB	82
Max air consumption	cfm	141,2
Air working pressure	psi	29 ÷ 87
Air inlet connection		NPT 3/4" (f)
Air outlet connection (muffler)		NPT 1" (f)
Fluid inlet connection		ANSI 150 - DIN PN 10 - JIS 10K 2" (1.97")
Fluid outlet connection		ANSI 150 - DIN PN 10 - JIS 10K 2" (1.97")
Balls for inlet and outlet		ball valve
Membranes		Santoprene <sup>™</sup>
Balls		Santoprene <sup>™</sup>
Seats		Santoprene <sup>™</sup>
Packing	No. - ft3	1 - 4.6
Gross weight	lb	110

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906