



P/N 43091-55

Waste oil gravity and suction drainers

Pneumatic waste oil drain with wheel-mounted 23.8 gal tank equipped with transparent chamber



FLUIDS SECTORS

WASTE OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

| Features | UM | Value |
|-----------------------------------|-----------|-------------|
| Tank capacity | gallons | 23,8 |
| Max draining capacity | gallons | 19,8 |
| Prechamber capacity | gallons | 2,1 |
| Bowl capacity | gallons | - |
| Air pressure for depressurisation | psi | 94 ÷ 102 |
| Depressurisation time | min | 2,5 ÷ 3 |
| Noise level | dB | 75 |
| Suction speed | gpm | 0.4 ÷ 0.5 |
| Total suction capacity | gallons | 15.9 ÷ 17.2 |
| Discharging/Suction hose | feet (') | 7/7 |
| Max pressure for discharging | psi | 7 |
| Set of probes | P/N | 45560-55 |
| Packing | No. - ft3 | 2 - 8.8 |
| Weight | lb | 79 |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc