



P/N 44060-55

Waste oil gravity and suction drainers

Combination pneumatic oil suction drainer 17.2 gal
without transparent chamber



FLUIDS SECTORS

WASTE OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	17,2
Max draining capacity	gallons	13,7
Prechamber capacity	gallons	-
Bowl capacity	gallons	4
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	2
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	11.4 ÷ 11.9
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	3 - 11.7
Weight	lb	76

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc