



# P/N 44084-55

## Waste oil gravity and suction drainers

Combination pneumatic oil suction drainer 21.1 gal  
without transparent chamber



### FLUIDS SECTORS

WASTE OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND  
ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	21,1
Max draining capacity	gallons	16,4
Prechamber capacity	gallons	-
Bowl capacity	gallons	-
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	2,5 ÷ 3
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	15.9 ÷ 17.2
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	2 - 6.7
Weight	lb	75

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906