



P/N 44091-55

Waste oil gravity and suction drainers

Combination pneumatic oil suction drainer 23.8 gal
with transparent chamber



FLUIDS SECTORS

WASTE OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	23,8
Max draining capacity	gallons	19,8
Prechamber capacity	gallons	2,1
Bowl capacity	gallons	3,9
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	2,5 ÷ 3
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	15.9 ÷ 17.2
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	3 - 12.7
Weight	lb	93

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc