P/N 44118-55

Gravity drainers with pantograph and on a pit

Combination pneumatic oil suction drainer 30.4 gal with transparent chamber, quick release connector and air regulator



FLUIDS WASTE OIL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	30,4
Max draining capacity	gallons	25,6
Prechamber capacity	gallons	2,1
Bowl capacity	gallons	4
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	3 ÷ 3,5
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	22.5 ÷ 23.8
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	3 - 16.2
Weight	lb	110

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc