# P/N 60280-55

## Grease dispensers

Portable lever-operated manual grease pumps for drums of 26 ÷ 40 lbs with external ø from 9.5" to 10"



**FLUIDS** GREASE

**SECTORS** AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

| Features | UM | Value |
|---|---|---|
| Suitable for drums | lb | 26 ÷ 40 |
| For drums with external ø | inches (") | 9.5 ÷ 10 |
| Delivery hose length | feet (') | 8 - 1/4" |
| Max grease outlet pressure | psi | 5000 ÷ 5800 |
| Capacity every 10 cycles of lever | lb | 0,13 |
| Drum cover | inches (") | 11 |
| Grease follower plate ø | inches (") | 10 |
| Grease coupler | P/N | 66739-55 |
| Packing | No. - ft3 | 1 - 0.8 |
| Weight | lb | 12 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc