P/N 62174-55

Grease pumps

Pneumatic pump series 238, R 50:1 - 3.3 lb/min with polyurethane seals, 29" suction tube length suitable for 120 lbs drums



FLUIDS	GREASE
SECTORS	AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

Features	UM	Value
Flow rate	lb/min	3,3
Ratio		50:1
Compatible fluids		greases, medium/high viscosity
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/4" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	87
Noise level	dB	81
Air max pressure	psi	120
Suction tube length	inches (")	29" - ø 1.18"
Suitable for drums	lb	120
Packing	No. - ft3	1 - 0.52
Weight	lb	14

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc