



P/N 68113-55

Grease dispensers

Wheel mounted manual grease pump, 29 lb tanks, high pressure



FLUIDS SECTORS

GREASE

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

Features	UM	Value
Tank capacity	lb	29
Delivery hose length	feet (')	8 -1/4"
Delivery hose	P/N	KR6802
Max grease outlet pressure	psi	5000 ÷ 5800
Capacity every 10 cycles of lever	lb	0,09
Pump	P/N	-
Compression ratio		-
Noise level	dB	-
Max working pressure	psi	-
Max air consumption	gpm	-
Capacity (free outlet 90 psi self-levelling grease at 68 °F)	lb/min	-
Grease follower plate	P/N	yes
Grease coupler	P/N	66739-55
Grease handle	P/N	-
Packing	No. - ft ³	1 - 2.5
Weight	lb	31

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc