P/N 68213-55

Grease dispensers

Pneumatic grease pump R 50:1, wheel-mounted with 29 lbs tank, follower plate, hose 1/4" - 13', air pump R 50:1 p/n 62141-55 and grease handle with rigid terminal



FLUIDS GREASE

SECTORS AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

Features	UM	Value
Tank capacity	lb	29
Delivery hose length	feet (')	13 - 1/4"
Delivery hose	P/N	993.504-55
Max grease outlet pressure	psi	5000 ÷ 5800
Capacity every 10 cycles of lever	lb	-
Pump	P/N	62041-55
Compression ratio		50:1
Noise level	dB	81
Max working pressure	psi	120
Max air consumption	gpm	87,1
Capacity (free outlet 90 psi self-levelling grease at 68 °F)	lb/min	2,2
Grease follower plate	P/N	yes
Grease coupler	P/N	66740-55
Grease handle	P/N	66882-55
Packing	No. - ft3	1 - 3.5
Weight	lb	37

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc