P/N 735000-55

Grounding cable reels - s. 350

Grounding reel series 350 fixed without cable, max cable capacity 98' - cross section 0.025 inches²



FLUIDS ELECTRICITY

SECTORS AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Information		grounding
Environment temperature	°F	23 ÷ 104
Number of conductors		1
Cable type		-
Conducting cable material		-
Conducting cable insulation		-
Cable cross section		-
Cable length	feet (')	max cable capacity 98' - cross section 0.025 inches²
Grounding pliers	P/N	-
Intensity pliers	A	-
Packing	No. - ft3	1 - 1.6
Weight	lb	23 ÷ 25

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

info@raasmusa.com - www.raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc