# P/N 8392.500-55

## AISI 304 stainless steel hose reels

AISI 304 stainless steel hose reel for grease, 5800 psi, without hose, NPSM 3/8" (f) inlet - NPTF 3/8" (f) outlet



| | |
|---|---|
| FLUIDS | GREASE |
| SECTORS | AGRICULTURE \| CLEANING \| CHEMICAL INDUSTRY \| MANUFACTURING INDUSTRY \| SHIPPING AND OFFSHORE |
| CERTIFICATIONS | ATEX (ZONE 1) \| ATEX (ZONE 21) |

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 5800 |
| Compatible fluids | | grease |
| Swivel joint | | zinc plated steel |
| Seals | | polyurethane |
| Characteristic | | fixed |
| Material | | AISI 304 stainless steel |
| Couplings | | - |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | NPSM 3/8" (f) |
| Outlet | | NPTF 3/8" (f) |
| Reel flow path | | zinc plated steel - AISI 304 stainless steel |
| Drum width | inches (") | 4.3" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc