



P/N 8532.500-55

AISI 304 stainless steel hose reels

AISI 304 stainless steel hose reel for grease, 5800 psi,
without hose, NPSM 3/8" (f) inlet - NPSM 3/8" (f) outlet



FLUIDS

GREASE

SECTORS

AGRICULTURE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL
INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	5800
Compatible fluids		grease
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		AISI 304 stainless steel
Couplings		-
Hose		-
Ø and hose length	Ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		zinc plated steel - AISI 304 stainless steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc