



P/N 89010-55

Enclosed hose reels with polyurethane hose

Hose reel for air-water, 300 psi, with polyurethane hose
36' ø 5/16", NPTF 1/4" (m) inlet - NPTF 1/4" (m) outlet



FLUIDS SECTORS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE | CLEANING DETERGENT
AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		swivelling
Material		technopolymer
Couplings		brass
Hose		971.111-55
ø and hose length	ø - feet (')	5/16" - 36'
Inlet		NPTF 1/4" (m)
Outlet		NPTF 1/4" (m)
Reel flow path		brass - zinc plated steel
Drum width	inches (")	4.3"

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906