# P/N 90D/21-55

## Industrial pumps - s. 900

Divorced pump series 312, R 2:1 - 25 gpm with polyurethane seals, 24.6"suction tube lenght



| | |
|---|---|
| FLUIDS | FRESH OIL \| ANTIFREEZE \| DIESEL FUEL |
| SECTORS | MANUFACTURING INDUSTRY \| MINING \| SHIPPING AND OFFSHORE |
| CERTIFICATIONS | ATEX (ZONE 2) \| ATEX (ZONE 22) |

| Features | UM | Value |
|---|---|---|
| Flow rate | | 25 gpm |
| Ratio | | 2:1 |
| Compatible fluids | | oils, lubricants and similar products |
| Suction tube upper body | | carbon steel |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/2" (f) |
| Fluid outlet connection | | NPT 1-1/2" (f) |
| Max supply pressure | psi | 120 |
| Max air consumption 120 psi | cfm | 71 |
| Noise level | dB | 80 |
| Suitable for drums or tank | | modular - bulk tank |
| Packing | No. - ft3 | 1 - 4.2 |
| Weight | lb | 99 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com


Copyright ® 2026 All rights reserved to RAASM USA, Inc