# P/N 91C/111-55

## Industrial pumps - s. 900

Pneumatic pump series 312, R 11:1 - 8 gpm or 33 lb/min, with polyurethane seals, 37" suction tube, suitable for 55 gal drums



**FLUIDS** FRESH OIL | GREASE

**SECTORS** AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

**CERTIFICATIONS** ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|---|---|---|
| Flow rate | | 8 gpm - 33 lb/min |
| Ratio | | 11:1 |
| Compatible fluids | | oils, lubricants and greases |
| Suction tube upper body | | aluminum |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/2" (f) |
| Fluid outlet connection | | NPT 3/4" (f) |
| Max supply pressure | psi | 120 |
| Max air consumption 120 psi | cfm | 64 |
| Noise level | dB | 80 |
| Suitable for drums or tank | | suitable for drums 55 gal |
| Packing | No. - ft3 | 1 - 3.3 |
| Weight | lb | 36 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc