# P/N 92708.101-55

## Enclosed hose reels with polyurethane hose

AISI 304 stainless steel enclosed hose reels series 250 for air-water, 290 psi, with polyurethane hose 40' ø 5/16", NPT 3/8" (m) inlet - NPT 1/4" (m) outlet



| | |
|---|---|
| FLUIDS | ANTIFREEZE \| WINDSHIELD FLUID \| AIR \| WATER \| NITROGEN/INFLATING USE \| CLEANING DETERGENT |
| SECTORS | AGRICULTURE \| CLEANING \| CHEMICAL INDUSTRY \| MANUFACTURING INDUSTRY |

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 300 |
| Compatible fluids | | air - water 70 °C |
| Swivel joint | | AISI 304 stainless steel - Delrin® |
| Seals | | Viton® |
| Characteristic | | swivelling |
| Material | | AISI 304 stainless steel |
| Couplings | | AISI 304 stainless steel |
| Hose | | 981.112-55 |
| ø and hose length | ø - feet (') | 5/16" - 40' |
| Inlet | | NPTF 3/8" (m) |
| Outlet | | NPTF 1/4" (m) |
| Reel flow path | | AISI 304 stainless steel - Delrin® |
| Drum width | inches (") | 4.9" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc