P/N 92F/451-55

Industrial pumps - s. 900

Flanged pump series 312, R 45:1 - 9.7 lbs/min with polyurethane seals, 29" suction tube lenght, suitable for 120 lb drums



FLUIDS FRESH OIL | GREASE

SECTORS AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		9.7 lb/min
Ratio		45:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	63
Noise level	dB	80
Suitable for drums or tank		suitable for drums 120 lb
Packing	No. - ft3	1 - 3.3
Weight	lb	40

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc