



P/N 95D/61-55

AISI 304 stainless steel industrial pumps

AISI 304 stainless steel divorced pump series 312, R
6:1 - 11 gpm, with Teflon® seals, 18.9" suction tube
length, modular



FLUIDS

ANTIFREEZE | WINDSHIELD FLUID | WATER | DEF | PAINT | CLEANING DETERGENT

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY
| MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate	gpm	11
Ratio		6:1
Compatible fluids		paints, chemical and industrial fluids
Suction tube upper body		AISI 304 stainless steel
Suction tube		AISI 304 stainless steel
Air inlet connection		NPT 1/2" (f)
Fluid inlet connection		NPT 1" (f)
Fluid outlet connection		NPT 3/4" (f)
Max air consumption 120 psi	cfm	64
Noise level	dB	80
Max supply pressure	psi	120
Suitable for drums or tanks		modular
Packing	No. - ft3	1 - 2.0
Weight	lb	37

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906